

KANGAROO ACRYLIC PRIMER (KSC307)

Acrylic Primer is a water-acrylic based primer and sealer, highly versatile, can be used as a bonding agent primer prior to application of any aqueous and/or cementitious based paints, mortars or waterproofing products, or used as a sealer to concrete and stone to enhance weathering, waterproofing and dustproofing.



Advantages

- Single component, ready to use and easy to apply.
- Versatile uses.
- Can be used as sealer to concrete and stone.
- penetrate into the concrete pores
- Increases bonding strength as a primer. Increases scratch and UV resistance as a sealer.
- Enhances surface waterproofing and dustproofing properties.
- Micro treatment of concrete and stone surfaces.
- Economic product, high concentrated.

Properties

Application temperature	5 – 35 °C
Base	Water - based
Flexural strength @ 28 days	≥ 1 MPa ISO 13007
Color	Milky White
Packaging	5 Ltr, 20 Ltr
Fire	Non-Flammable



Way of Use

Substrate Preparation

The substrate should be sound, clean, and free from contamination. Surface laitance should be removed mechanically to prevent any weakness in the substrate.

Application

1. Ensure surface to be sealed is clean, firm, dust and oil free. Acrylic Primer may be applied to damp surfaces.
2. Apply Acrylic Primer with roller, brush or spray.
3. Leave to penetrate for 1 hour before applying other materials next, do not leave for more than 8 hours when used as a primer.
4. For use as a sealer, apply 2 coats with 10 hours in between.

Cleaning:

Clean with water.

Cautions

Health and Safety: **Acrylic Primer** is a non-toxic liquid but may be irritating to the eyes or skin. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep container in a well-ventilated place.

In case of contact with eyes, rinse immediately with plenty of water. If swallowed, seek medical advice immediately and show this container or label.

Storage

Acrylic Primer has a shelf life of 12 months from date of manufacture.

The best storage temperature is between 5°C and 30°C away from sun light.

